

# Eccostock®Adhesive 13111

# One-Part Solvent Based Contact Adhesive



## **ONE-PART SOLVENT BASED CONTACT ADHESIVE**

Eccostock Adhesive 13111 is a one-part CFC-free general purpose glue. It is a sprayable glue based on a synthetic rubber. Eccostock 13111 provides good adhesion to neoprene, natural and synthetic rubber, nylon, glass, ceramic, wood, PVC, insulation materials and most plastic materials.

#### **FEATURES AND BENEFITS**

- Good adhesion
- Sprayable

#### **MARKETS**

- Commercial Telecom
- Security and Defense
- Test & Measurement

### **SPECIFICATIONS**

TYPICAL PROPERTIES	ECCOSTOCK ADHESIVE 13111
Best Service Temperature °C(°F)	18 – 20 (64.4 – 68)
Solvent	Light inflammable (ethylacetate/acetone)
Density, g/cc	0.8
Estimated Coverage per liter	2 m²

#### **APPLICATIONS**

- Eccostock Adhesive 13111 is the recommended adhesive for bonding our Eccosorb foam absorbers.
- It can be used to attach foam absorbers to different substrates.

# **AVAILABILITY**

- Eccostock Adhesive 13111 is standard available in 1 liter and 5 liter containers.
- Country of Origin : Belgium, Europe

# **INSTRUCTIONS FOR USE**

- All surfaces to be bonded, except foam type absorbers and similar porous surfaces, should be cleaned of oil, grease and any foreign matter by means of a clean cloth dipped in an industrial cleaner degreaser solution.
- Apply with good ventilation, avoid excessive breathing of vapours and wear individual adapted safety equipment.
- Shake well before opening and mix thoroughly before use.
- Best service temperature: 18 to 20°C.
- Sprayable glue.
- Both surfaces to be bonded must be spray coated.
- Open time: 5 to 20 minutes according to applications.
- Apply sufficient pressure to ensure good contact to the mating surfaces.

#### Storage conditions:

- Shelf life is 6 months when stored in closed, well sealed containers.
- Conserve at a temperature of min 10°C in a dry place.

Asia: +86.755.2714.1166

Americas: +1.866.928.8181

Europe: +49.(0)8031.2460.0

RFP-DS-Adhesive13111 120315

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies 'Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies (or any third party intellectual property of third party intellectual property rights.